

Naziv PDF datoteke



DPX 250 LEGRAND

Isolating switch DPX-IS 250 with release, 3 poles, rated current of 160A with front handle

REF. 026632 | EAN KODA. 3245060266325

DPX-IS isolating switch for on-load circuit breaking by visible isolation and positive contact action

> [The product details page](#)

Splošni opis:

DPX-IS isolating switch for on-load circuit breaking by visible isolation and positive contact action

Značilnosti izdelka:

- Suitable for commercial and middle power installations, according to EN/IEC standard 60947-3 - Compliant with NEMA AB-1
- Category f use AC23
- Rated insulation voltage of 800V - Rated impulse withstand voltage of 8kV
- Connection with cage terminals, supplied with terminal shields
- Padlock integrated in the handle - Can be equipped with emergency use handle or vari-depth handle

Prednosti montaže:

- DPX³-IS 250 can be mounted on DIN rail or on plate in XL³ or XL³ S enclosures

Prednosti uporabe:

- Climatic condition according to IEC/EN 60947-1 Annex Q, Cat. F subject to temperature, humidity, vibration, shock and salt mist

Dokumentacija

Tehnična dokumentacija

 F00697FR_03.pdf | PDF (0.63Mo)

 Y2376B.pdf | PDF (0.82Mo)

 F00697EN_03.pdf | PDF (0.63Mo)

CAD & specifikacije načrtov / BIM

 026607.dwg | DWG (0.14Mo)

Katalog & drugo

 ex223001_0248.pdf | PDF (0.08Mo)

 ex223001_0254.pdf | PDF (0.03Mo)

 ex223001_0249.pdf | PDF (0.11Mo)

Pogodbe in certifikati

 OC / CB-SE-106716 | (0.09Mo)