

Naziv PDF datoteke



LEGRAND

KNX PIR HD PRESENCE SENSOR - CEILING MOUNTED - 360° - IP20

REF. 048922 | EAN KODA. 3245060489229

[> The product details page](#)

Značilnosti izdelka:

- 360° passive infrared and ultrasound detection, range 8 m
- IP 20
- Consumption 0,5 W
- Connection by KNX red/black connector

Priporočila / omejitve

- Configuration through ETS tool from KNX association
Optimum distance between two sensors: 6 m

Prednosti montaže:

- Fixes directly in suspended ceiling with springs (supplied) or is installed in a 50 mm deep Batibox Surface mounted on ceiling using accessory Cat.No 0 488 75 Connected with the BUS/KNX cable

Prednosti uporabe:

- Special presence sensors for small work areas - individual offices

Edinstvene značilnosti:

- Constantly check for presence and light levels, switching OFF as soon as the natural light level is sufficient Switch ON and OFF automatically
- Accurate set-up on site with configuration device
- Because a broad range of KNX devices communicate with each other, (even if they are from different manufacturer) KNX technology answers to high demands for smart home or building thanks to endless flexibility and personalization

Dokumentacija

Tehnična dokumentacija

 LE05504AC_FR.pdf | PDF (6.12Mo)

 LE08201AC.pdf | PDF (0.73Mo)

 LE05504AB_EN.pdf | PDF (2.96Mo)

 S000089365EN_2.pdf | PDF (2.82Mo)

CAD & specifikacije načrtov / BIM

Legrand_Gestion_eclairage_Detecteur_Presence_Plafond_KNX.rfa

Katalog & drugo

 ex223001_0895.pdf | PDF (0.06Mo)

Pogodbe in certifikati

 KNX EIB-11/11783/14 | (0.18Mo)

| RFA (0.78Mo)
Legrand_Lighting_Management_KNX_Presence_Sensor_Ceiling.rfa
| RFA (0.79Mo)

Oznaka besedila

-  FW_LG-048922.zip | ZIP (0.05Mo)
-  FW_LG-002638_2.zip | ZIP (8.46Mo)