

Naziv PDF datoteke



PLEXO™ LEGRAND

Plexo™ - german standard socket outlet with auto terminals 16A 250V - Mechanism - Grey

REF. 069570L | EAN KODA. 3414971879164

The grey Plexo composable waterproof socket-outlet can be used to connect electrical or electronic equipment in any location where resistance to water, dust and impact is required. For indoor or outdoor use.

> [The product details page](#)

Splošni opis:

The grey Plexo composable waterproof socket-outlet can be used to connect electrical or electronic equipment in any location where resistance to water, dust and impact is required. For indoor or outdoor use.

Značilnosti izdelka:

- Product to be completed either with a surface-mounted box or a flush-mounted support frame.
- IP55 : protected against dust and water spray from all directions
- IK08: 5 joules shock resistance.
- 2P+E 16A 250V socket outlet. Automatic terminals : quick connection without tools with colour coding.

Prednosti montaže:

- A 90° symmetrical socket mechanism for horizontal or vertical mounting on surface-mounted boxes or flush-mounted support frames. The mechanism is easy to install without tools and can be removed by simply pressing on the sides. The clipping system ensures high resistance to wire pressure.

Edinstvene značilnosti:

- A 90° symmetrical mechanism for horizontal or vertical mounting on surface-mounted boxes or flush-mounted support frames.
- A 4-point (1/4 turn) front closure to ensure waterproofness whatever the configuration of the installation.

Dokumentacija

Tehnična dokumentacija

 F03972FR-00.pdf | PDF (0.96Mo)

 F04054EN-00.pdf | PDF (0.96Mo)

 F03972EN-00.pdf | PDF (0.96Mo)

CAD & specifikacije načrtov / BIM

 3D_LG-069570L.stp | IFC (1.36Mo)

BIM-LEGRAND-MOSAIC-2025-FRANCAIS.rvt | RVT (124.38Mo)

BIM-LEGRAND-MOSAIC-2025-ENGLISH.rvt | RVT (125.73Mo)

Katalog & drugo

 ex223001_0794.pdf | PDF (0.11Mo)

Pogodbe in certifikati

 OC / CB-FR_718712/A1 | (0.55Mo)

 AENOR-030/002645 | (0.59Mo)

 SNI-824 220292 | (0.49Mo)

 KSC-JW04001-24001 | (3.79Mo)

 VDE-40059394 | (0.44Mo)

