

Naziv PDF datoteke



LINKEO LEGRAND

Intelligent PDU, metered (Node version), Zero-U, 1 phase 32A, 36 HD C13 outlets + 6 C19 outlets, with cord locking

REF. 646109 | EAN KODA. 3414972245715

> [The product details page](#)

Značilnosti izdelka:

- 1 phase - 32A - Max power 7,4kW
- 36 High Density C13 outlets + 6 C19 outlets, with cord locking system
- Metering at inlet and circuit level with +/- 1% accuracy (Voltage, Current, Active Power, Apparent Power, Energy, Power Factor)
- Supplied with a hot swappable full IP controller (NODE) with LCD screen to manage and view information locally, and with a Ethernet port for connection to LAN and remote control.
- 3 m power supply cord with IEC 60309 32A plug

Prednosti montaže:

- Easy installation thanks to the 330° rotating cable input for a perfect orientation of the cable and no interference in the cabinet. Numbered outlets to ease the identification of each server. Supplied with 2 sets of metal fixings: button for screwless fixing, or standard screw-type brackets.

Prednosti uporabe:

- Reduce your CAPEX and deploy intelligent PDUs without the need to have a PDU controller in every unit. Reduce your OPEX by daisy-chaining up to 31 base PDUs downstream to a node PDU to save switch ports connections. User-friendly and responsive Web User Interface. Metering, outlet Control and peripherals data at glance. Easy to configure. Data aggregation capabilities in DCIM.

Edinstvene značilnosti:

- 2 levels of alerts physically visible on the PDU (LED bar) and remotely (web interface and email/sms alert configuration)
- Possibility to add up to 8 wireless sensors (temperature, humidity...) for environmental monitoring. Using wireless sensors reduce deployment and maintenance time.
- Node controller is hot swappable to allow maintenance or replacement without powering down connected equipment

Dokumentacija

Tehnična dokumentacija

Katalog & drugo

-  FT-646109-FR-02.pdf | PDF (2.38Mo)
-  FT-646109-EN-02.pdf | PDF (2.37Mo)
-  User_Guide_Linkeo_DC_PDUUs_4.0.35.pdf | PDF (8.97Mo)
-  User_Guide_Linkeo_DC_PDUUs_4.0.34.pdf | PDF (8.92Mo)
-  LE13286AE.pdf | PDF (3.62Mo)

CAD & specifikacije načrtov / BIM

- PDU metered 0U.rfa | RFA (2.66Mo)
- Metered PDU 0U.rfa | RFA (2.66Mo)

Oznaka besedila

-  PDU_LDC_040034-50319_Firmware.bin | BIN (16.22Mo)
-  PDU_LDC_040031-49324_ReleaseNotes.pdf | PDF (0.23Mo)
-  PDU_LDC_040034-50319_ReleaseNotes.pdf | PDF (0.86Mo)
-  PDU_LDC_040035-50602_Firmware.bin | BIN (16.18Mo)
-  PDU_LDC_040031-49324_Firmware.bin | BIN (16.21Mo)
-  PDU_LDC_040035-50602_ReleaseNotes.pdf | PDF (0.86Mo)

-  ex223001_1040.pdf | PDF (0.37Mo)

Pogodbe in certifikati

-  LGRP-01652-V03.01-EN.pdf | PDF (1.72Mo)
-  Decl. UE RED-O 449 C | (0.6Mo)
-  LGRP-01652-V03.01-FR.pdf | PDF (1.69Mo)